

T7920, *Riser Specification sheet*

April 14, 2020

T7920 Riser

Depending on your system configuration, the following PCI Express (PCIe) generation 3 expansion cards are supported: Figure 1. *Dell*.

PCIe slots on the riser	Processor connection	Height	Length	Link	Slot width
Slot 1	Processor 1	Full Height	Full Length	x16	x16
Slot 2	Processor 1	Full Height	Full Length	x16	x16
Slot 3	Processor 1	Full Height	Full Length	x8	x8
Slot 4	Processor 1	Full Height	Full Length	x4	x16
Slot 5	Processor 1	Full Height	Full Length	x1	x16
Slot 6	Processor 2	Full Height	Full Length	x16	x16
Slot 7	Processor 2	Full Height	Full Length	x16	x16

Figure 1: T7920 Riser Configuration.

T7920 Drive Bays

The T7920 has a configurable Flex bays. the T7920 has Four Flex bays (0,1,2,3) and 5.25" Drive bay. This 5.25" can also be converted to allow for an extra two drives. The total number of drives that can fit inside the chassis is Ten. Two Flex bays can also be converted into an extra 5.25" as well. The following table shows these different configurations:

CONFIGURATION	SAS/SATA	PCI-E 3
1	4	0
2	0	4
3	8	0
4	0	8
5	10	0
6	0	10
7	2	2
8	2	4
9	4	2
10	4	4
11	6	4
12	4	6
13	8	2
14	2	8

Figure 2: T7920 Drive Bay Configurations.